



Electrodes / Pouch  
Electrodes / Case

## APPLICATION

For: Hours

## PRODUCT INFORMATION

Shape  
Size (excl. grip)  
Sensor (Eyelet) Diameter  
Substrate Thickness (adapter excluded)  
Total Product Surface Area  
Gel Area  
Adhesive Area  
Integrated Lead Wire (length / color)

## MATERIALS

Substrate Material  
Adhesive  
Gel Type  
Foam (Sponge) Material  
Release Liner  
Sensor Polymer  
Adaptor / Connector (Stud)  
Integrated Lead Wire Jacketing  
Integrated Lead Wire Cord

## ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

<b>ACZ impedance</b> (before defib simulation) @10 Hz	Ohm
<b>DC Offset Voltage</b> (before defib simulation)	mV
<b>SDR Slope</b> (remaining potential after defib) @ 30 Sec int.	mV/sec
<b>ACZ impedance repeat</b> (after defib simulation)	Ohm
<b>COIIN</b> (combined offset instability and inner noise)	µV
<b>Bias Current Tolerance</b> (DC offset voltage after DC loading)	mV

## FEATURES

MR Conditional  
X-ray Translucence  
Integrated Abrader  
Repositionability

## PACKAGING

<b>Product Packaging Material</b>	
<b>Resealable Pouch</b>	
<b>Product Packaging Size (L x W)</b>	in cm
<b>Department Packaging - Box (L x W)</b>	in cm
<b>Transport Packaging - Carton (L x W)</b>	in cm

## BIOCOMPATIBILITY

ISO 10993  
Latex Free

## ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)  
Phthalate Derivatives Content (e.g. DEHP)  
RoHS Compliant  
REACH Compliant

## SHELF LIFE

**Product Shelf Life** (in accordance with storage guidelines)

## REGULATORY STATUS

**Reorder Part Number:**